

# ALPHA 9000 SERIES - 9030V



## P3 DISPOSABLE RESPIRATOR

A traditional range of lightweight cup shape respirators offering excellent value.

### KEY FEATURES

- Range tested to 'Dolomite Clogging Test (D)'
- Soft inner nose seal
- Traditional metal nose clip adjustment
- Soft, lightweight fabrics
- Low profile valve reduces exhalation resistance keeping the wearer cooler
- Conforms to EN149: 2001 + A1 : 2009



### ORDERING INFORMATION

**Part Number:** 9030V

**Packaging:** 5 singles per box  
12 boxes per case

**Certification:** EN149: 2001 + A1 : 2009  
FFP3 NR D

### SUITABLE APPLICATIONS

Recommended applications include:

- Craft work
- Cutting & Casting of Metals
- Disposal of Toxic Waste
- Hospital
- Iron & Steel Industry
- Laboratory & Disease Control
- Manufacture of Batteries (Ni-Cad)
- Mining
- Pharmaceutical Industry
- Textile Industry
- Underground Civil Engineering
- Welding Work
- Woodworking

# ALPHA 9000 SERIES - 9030V



## P3 DISPOSABLE RESPIRATOR

### TECHNICAL SPECIFICATIONS

#### MATERIALS

COMPONENT	MATERIAL
<b>Outer Cover:</b>	Polypropylene Fabric
<b>Filter Media:</b>	High Filtration Efficiency Melt-Blown (Polypropylene)
<b>Inner Cover:</b>	Polyester Fabric
<b>Nosebridge:</b>	Aluminium
<b>Nosefoam:</b>	PVC Foam
<b>Headstrap:</b>	Knitted Elastic Band
<b>Exhalation Valve:</b>	Valve Housing - Polypropylene Valve Membrane - Synthetic Rubber

#### DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
<b>Respirator:</b>	139	127	54
<b>Nosebridge:</b>	90	5	0.5
<b>Nosefoam:</b>	139	127	2
<b>Headstrap Upper:</b>	540	10.55	1.5
<b>Headstrap Lower:</b>	460	10.5	1.5
<b>Exhalation Valve:</b>	41 (Diameter)	-	11

### CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands. [N.B. No.2797].

### RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

### PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149:2001 + A1:2009	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	Odours / Org. Vapours (Below WEL)	VeryFine / Toxic Dusts / Mists / Fumes	Metal Fumes	Oil/Water Based Particulates
FFP1 NR D	9010	4	■					■
FFP1 NR D	9010V	4	■					■
FFP2 NR D	9020	10	○	■			○	■
FFP2 NR D	9020V	10	○	■			○	■
FFP2 NR D	9020W	10	○	■	■		■	■
FFP3 NR	9030V	20	○	■		■	■	■

■ = Recommended ○ = Alternative

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Alpha Solway Ltd

Part of  
**Globus**  
GROUP